

DISCOFIX

6m working width

from

TECHNIK-PLUS



Discofix-3m is a combination with pneumatic seeder „Turbo Jet Super“, fan HC+CO2 und disk harrow

TP TURBO-JET SUPER 11

Standard / electric blower




11outlet; 60m flexible plastic hose diam 25mm; **hopper as required 130-, 200-, 300-, 400-Lit.** (transparent) with engraved liter scale. Y-dividens to place need on 22 outlets, lid with seal, blower electric, adjustable seedroll flap, agitator, seedroll for use of different seeds, standard seedroll, metal seedroll, single speed seedroll motor;

FAN:

QUATTRO-FAN-TECHNIK

reinforced=required 50 Ampere:

ELEKTRIC, 2 x double blower (=4 blower),
6.500 rotations per minute.



Control unit (in the cab):

PROFI (included as standard):

ON/OFF, Stepless adjustment of speed on seedroll motor
(20-70 rpm) = adjustment of seed rate.

Blower **ON/OFF**, **ON/ OFF Sensor automatic**, seedroll
controlsensor operation control light for blower.



or

SEEDER+CONTROL UNIT:

Fully automatic, driven speed,
independent, incl. Speed sensor,
inkl. **ON/OFF** sensor length of
cables 7m



FRAME WITH DISCS

Working width 6 m

Hot galvanized frame

22 Disc holder frames for fitting 44 discs (13,6 cm cutting gap row).

Front and rear three point frame.

Possibility to fit roller or any other equipment. Front levelling bar

120 x 120mm, hight adjustable 44 springs

Profiles reinforced. 22 Disc holder bracket.

In the bracket fitted seed placement distributor. Adjustable cut angle of discs=

in driveline and horizontal. Bracket for placement of exhaust gas onto ground and

into cutted gap. Adjustable bar to hold spring tines for closing of gap gap with loose soil.

All parts produced, that on basic can be adapted each further module required.

22 braket to hold one pair discs=44 discs with angle plates. 22 seed placement brakets inox

22 exhaust gas distributor. Hoses for exhaust

gas distributor, metal hoses DM30mm



Fitting brakets for Turbo Jet Super 11 with safety stairs. Podest for easy hopper filling. Safety hadrail galvanized.

3

CO₂ - FAN

For placing the exhaust gas from tractor into soil during cultivation

HYDRAULIC DRIVEN BLOWER

- 1 inlet Ø 100mm
- 1 outlet Ø 100mm into steel tube connections to folding sections
- 1 Fan Ø 395mm

Hydraulic motor with oil hoses, flow motor

max. 15 lit/min, system max flow 50 lit/min

mounting bracket for fan with metal hose

DM 100 mm quick coupling at blower inlet.

90° elbow collector tractor side, heavy hose clamps.

Mounting bracket to be designed especially locally.



Combination 6m DISCOFIX with pneumatic seeder "TP Turbo Jet Super 11" and Profi control unit



6m Combination DISCOFIX with pneumatic seeder and Profi control unit or control unit SEEDER



4

Contact:

Technik-Plus Sämaschinen e.U.

Industrieparkstrasse 6-8

8480 Mureck

AUSTRIA

Tel: +43 (0) 3472 21120

Fax: +43 (0) 3472 21123

E-Mail: t.kukovec@technik-plus.eu

E-Mail: technik-plus@technik-plus.eu